



LUXURIOUS SHEEN EMULSION

PRODUCT NAME :	PAR SILK
DESCRIPTION :	PAR Silk by Kansai is a premium grade emulsion that gives a brilliant, smooth and luxurious silk finish for interior use. Formulated with special emulsions, PAR Silk can withstand moderate washing which makes it ideal for surfaces where regular cleaning is required. PAR Silk is formulated to last longer than ordinary emulsion.
DESIGNED USE :	For use on new or previously painted interior masonry surfaces such as brickwork, plaster, cement rendering and asbestos cement where regular cleaning is a pre-requisite.
BINDER TYPE :	Premium grade acrylic binder pigmented with chalk resistant titanium dioxide and other high grade pigments.
PERFORMANCE :	<ul style="list-style-type: none"> ▪ High grade emulsion - outlast ordinary emulsion. ▪ Withstand moderate washing. ▪ Dirty hand marks can be wiped clean easily. ▪ Bright, smooth, luxurious finish. ▪ Excellent colour retention. ▪ No added lead or mercury.
PHYSICAL PROPERTIES :	
Coverage*	10 – 12 m ² /Lt @ 25 microns
Volume Solids	40%
Dry Film Thickness	25 microns / coat
Wet Film Thickness	63 microns / coat
Flash Point	Not applicable
FINISHING :	
Colours	See PAR by Kansai Colour Card.
Finish	Attractive silk sheen.
Pack Size	5 litres.
APPLICATION :	
Drying Times	Surface dry : 10 min ; Recoat : 1 - 2 hours.
Dilution	Clean household water.
Cleaning Up	Clean household water.
DILUTION RATIO :	
Brush or Roller	Ready for use. If dilution is required, add up to 5% clean water.
Conventional Spray	Dilution up to 10% water.
Airless Spray	Ready for use.
SPRAY EQUIPMENT GUIDE :	
Conventional Spray	A typical set up would be a minimum atomising pressure of 2.8 kg/cm ² and fluid pressure of 0.4 kg/cm ³ with a nozzle size of 0.43 mm.
Airless Spray	A typical set up would be a minimum of 155 kg/cm ³ with nozzle size of 0.38 - 0.43 mm and a spray tip angle of 65°.
	<div style="display: flex; justify-content: space-around; align-items: flex-end;"> <div style="text-align: center;">  <p>Application method</p> </div> <div style="text-align: center;">  <p>10-15 min drying time</p> </div> <div style="text-align: center;">  <p>65° spraying tip</p> </div> <div style="text-align: center;">  <p>Practice proper cleaning</p> </div> </div>

SURFACE PREPARATION

New, unpainted surfaces

Allow surfaces to cure and dry out at least 28 days. Large cracks must be repaired with cement: sand mix and rendered smooth. Make good all minor defects with appropriate fillers. Remove all loosely adhering residues by thorough brushing.

Repainting

Check for powders or chalk. These surface contaminants must be completely removed by washing with warm water and detergent solutions. Rinse with clean water, taking care to change the rinsing water regularly. If after thorough preparation the surface is still slightly powdery, it may be necessary to seal it with PAR Plasterseal DPP 1001 Solvent Based Wall Sealer. Dilute the sealer up to 30% and apply liberally to allow the sealer to fully penetrate the surface and form a barrier that seals up the chalk.



Seal a coat with primer



Use abrasive paper



Dust off

RECOMMENDED PAINT SYSTEM

New, unpainted surfaces



Repainting



NB : PAR Primer Sealer DPP 1035 and PAR Plasterseal DPP 1001 work best on surfaces with a moisture content of below 15% and alkalinity below pH-9, otherwise premature paint failure may occur.

Limitations

- Not suitable for use in areas subject to frequent or heavy condensation, e.g. in some kitchens and bathrooms.

SAFETY & HEALTH INFORMATION

- Ensure adequate lighting and ventilation during application and drying.
- This product does not contain added lead or mercury.
- When applying paints, it is advisable to wear eye protection.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Use soap and water to remove splashes from skin.
- Storage : Keep container closed and store in clean and dry conditions.
- Do not empty into drains or water courses.
- This product is not flammable. Keep out of reach of children.
- Chemical Safety Data Sheet (CSDS) is available upon request.



Keep seal tight



Secure upright



Wear proper protection



Practice proper disposal

For further information on Product Data, please contact:

Decorative Sales Department

Kansai Paint Asia Pacific Sdn. Bhd. (705919-W)
(formerly known as Kansai Coatings Malaysia Sdn. Bhd.)

9-1 & 9-2, Level 9, Port Tech Tower, Jalan Tiara 3/KU1, Bandar Baru Klang, 41150 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 6(03) 3002 4001 Fax: 6(03) 3002 4002

* Practical coverage will vary according to the roughness and porosity of surface to be painted, the application method and condition, dry film thickness and the skill of applicator.

The information in this technical data sheet is given to the best of our knowledge based on laboratory testing and practical experience and is provided as a general advice only. No guarantee of results is implied since the conditions of use are beyond our control. It is the responsibility of the users to ensure the suitability and proper usage of the product. We reserve the right to change the data without prior notice.