

KANPE ROAD MARKING PAINT

ALKYD & CHLORINATED BASED PAINT FOR MARKING

Product Name	KANPE ROAD MARKING PAINT						
Product Description	A highly durable road marking paint based on alkyd and chlorinated rubber.						
Designed Use	For road lines and signs marking						
Performance	<ul style="list-style-type: none"> • Good skid resistance • Excellent durability against abrasion • Strong adhesion to asphalt and concrete • Very fast drying 						
Physical Properties							
Theoretical Coverage*	8 – 10m ² / litre @ 60 µm DFT						
Volume Solids	60%						
Dry Film Thickness	60 µm DFT						
Wet Film Thickness	100 µm WFT						
Flash Point	26°C						
Finishing							
Colours	White, Yellow, Red, Blue, Green & Black						
Finishing	Matt						
Pack Size	5 liters						
Practical Application							
Drying Times	Surface Dry: 20 minutes Recoat: 2 hours (overnight for the best results)						
Dilution	810-1207 Thinner						
Cleaning Up	810-1207 Thinner						
Dilution Ratio							
Brush & Roller	0 – 5 %						
Conventional Spray	5 – 10 %						
Airless Spray	0 – 5 %						
Surface Preparation							
	<u>Asphalt and Concrete</u>						
	Surfaces must be clean, dry and free from all defective or poorly adhering materials. Previously painted surfaces must be thoroughly free of oil remove all grease and wax.						
Recommended Paint System							
	<u>New unpainted surfaces:</u>						
	<table border="1"> <thead> <tr> <th>1st coat</th> <th></th> <th>2-3rd coat</th> </tr> </thead> <tbody> <tr> <td>Kanpe Road Marking Paint</td> <td>Recoat after 2 hours</td> <td>Kanpe Road Marking Paint</td> </tr> </tbody> </table>	1 st coat		2-3 rd coat	Kanpe Road Marking Paint	Recoat after 2 hours	Kanpe Road Marking Paint
1 st coat		2-3 rd coat					
Kanpe Road Marking Paint	Recoat after 2 hours	Kanpe Road Marking Paint					
Storage	Store in cool dry place, avoid direct sunlight and keep away from naked flame and reach of children.						
Shelf Life	24 months under normal condition						

Health & Safety

This product contain solvent. Ensure adequate lighting and ventilation during application and drying. Do not use in confined spaces. Keep windows and doors open at all times.

- This product does not contain added lead or mercury.
- When applying paints, it is advisable to wear eye protection.
- In case of contact with eyes, rinse immediately with plenty of water and see medical advice.
- Use soap and water to remove splashes from skin.
- Storage: Keep container closed and store in clean and dry conditions.
- Do not empty into drains or water courses.
- This product is flammable. Keep out of reach of children.
- Safety Data Sheet (SDS) is available upon request.



Keep seal tight



Secure upright



Wear proper protection



Practice proper disposal

For further information on Product Data, please contact:

**Chin Leong Construction Systems Pte Ltd
(Exclusive Distributor of Kansai Paint)**

No.2 Tanjong Penjuru Singapore 609017

Tel.: +65 6265 2788 / Fax: +65 6268 6675

Website: www.kansaipaint.sg

*Practical coverage will vary according to the roughness and porosity of surface to be painted, the application method and condition, dry film and thickness and the skill of applicator.

The information in this technical data sheet is given to the best of our knowledge based on laboratory testing and practical experience and is provided as a general advice only. No guarantee of results is implied since the conditions of use are beyond our control. It is the responsibility of the users to ensure the suitability and proper usage of the product. We reserve the right to change the data without prior notice.